

# BAL HARBOUR

- V I L L A G E -

BAL HARBOUR BUILDING DEPARTMENT  
655-96TH STREET BAL HARBOUR, FLORIDA 33154  
TELEPHONE 305.866.4633

## Flooring Permit Affidavit

All commercial properties, including condominium units, are required to obtain a permit for flooring (tile, wood, marble). To obtain a permit for flooring please provide the following documents to the permit counter.

- 1) Permit Application
  - 2) Two copies of signed and notarized Flooring Permit Affidavit
  - 3) Two copies of the soundproofing manufacturer's literature with assembly value that complies with the Florida Building Code highlighted
  - 4) Two copies of Floor Plan indicating the area of work
  - 5) Copy of a notarized Contract/Agreement between client and contractor
- No review will be required for flooring permits with the exception of balcony/terraces, porches, bathrooms, lobbies, other public spaces and interior.

**NOTE: A soundproofing inspection is mandatory in the City of Bal Harbour**

### FLOORING PERMIT AFFIDAVIT

Process # \_\_\_\_\_

Address of Property \_\_\_\_\_

Product/Material \_\_\_\_\_

I, \_\_\_\_\_, the qualifying agent # \_\_\_\_\_ for \_\_\_\_\_  
(Name) (Contractor License Number) (Company Name)

hereby certify that all requirements of the Florida Building Code, Chapter 12, Section 1207 – Sound Transmission, will be met for the above mentioned location.

1207.2 Air-borne sound. Walls, partitions and floor/ceiling assemblies separating *dwelling units* from each other or from public or service areas shall have a sound transmission class (STC) of not less than 50 (45 if field tested) for air-borne noise when tested in accordance with ASTM E 90. Penetrations or openings in construction assemblies for piping; electrical devices; recessed cabinets; bathtubs; soffits; or heating, ventilating or exhaust ducts shall be sealed, lined, insulated or otherwise treated to maintain the required ratings. This requirement shall not apply to *dwelling unit* entrance doors; however, such doors shall be tight fitting to the frame and sill.

1207.3 Structure-borne sound. Floor/ceiling assemblies between *dwelling units* or between a *dwelling unit* and a public or service area within the structure shall have an impact insulation class (IIC) rating of not less than 50 (45 if field tested) when tested in accordance with ASTM E 492.

Signature: \_\_\_\_\_

Print Qualifier Name: \_\_\_\_\_

State of \_\_\_\_\_, County of \_\_\_\_\_  
Sworn to and subscribed before me this \_\_\_\_\_, Day of \_\_\_\_\_, 20\_\_\_\_\_

By \_\_\_\_\_

(SEAL) \_\_\_\_\_

Personally known or Produced Identification

Type of Identification \_\_\_\_\_

Attach:

-Copy of soundproofing manufacturer's literature with assembly value that complies with the Florida Building Code highlighted

-Floor Plan indicating the area of work

-Copy of Contract/Agreement between client and contractor